



MATERIAL:BRASS
 THICKNESS:0.2
 HARDNESS:SH
 APPLICABLE WIRE:(AWG)22-28
 PLATING:TIN 40μ" MIN.
 INSULATION O.D.:1.75 MAX.
 MATE:0.25*(0.635MM)SQUARE PIN
 CONTACT RESISTANCE:INITIAL VALUE/10mΩ max.
 AFTER ENVIRONMENTAL TESTING/
 20mΩ max.
 INSULATION RESISTANCE:1.000MΩ min.
 WITHSTANDING VOLTAGE:1.000V AC/minute
 VOLTAGE RATING:AC,DC,250V
 CURRENT RATING:AC,DC,3A
 TEMPERATURE RANGE : -25°C TO +85°C

DIMENSION:(MM)
 T:0.2±0.03
 L:6.6±0.25
 E:2.0±0.25
 W:1.85^{+0.15}_{-0.1}
 IS:3.0±0.3
 WS:1.8±0.3
 H:3.2±0.25
 H1:1.4±0.25
 H2:2.3±0.15
 t:0.7^{+0.15}₋₀
 e:2.5±0.15

APPD. 核准 Angel		SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 2.5mm TERMINAL BRASS MATERIAL TIN PLATING AWG22~28 1ROLL=8000 PCS ROHS LOW-LEAD
DWG. 製圖 Yumi				
DATE 制表日 2010/12/23		PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 T7000-TBJ00000R

RoHS Compliant **HSM** 玄茂科技股份有限公司
 HSIUAN MAO TECHNOLOGY CO., LTD.