



- 1.CABLE:NO UL.,28AWG(7/0.12±0.008mm),TINNED AND STRANDED COPPER WIRE  
 INSULATOR:PVC,ID:0.85mm ,CABLING:9C+DRAIN WIRE  
 SHIELD:AL/MY COVERAGE  
 JACKET:PVC,COMPLIANCE ROHS,COLOR:BEIGE,D.D:5mm
- 2.1PCS CONNECTOR:D-SUB 9 WAYS MALE SOLDER TYPE CONNECTOR  
 INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE  
 CONTACT:COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED  
 SHELL:NICKEL PLATED.  
 CONNECTOR COMPLIANCE ROHS
- 3.1PCS CONNECTOR:D-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR  
 INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE  
 CONTACT:COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED  
 SHELL:NICKEL PLATED.  
 CONNECTOR COMPLIANCE ROHS
- 4.HOOD:ASSEMBLY TYPE DB9 PIN PLASTIC COVER WITH SMALL SCREW  
 COLOR:BEIGE,COMPLIANCE ROHS
- 5.Fulfill ROHS Guideline
- 6.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

PIN OUT

| DB9PIN MALE(P1) | WIRE       | DB9PIN FEMALE(J1) |
|-----------------|------------|-------------------|
| 1               | =====      | 1                 |
| 2               | =====      | 2                 |
| 3               | =====      | 3                 |
| 4               | =====      | 4                 |
| 5               | =====      | 5                 |
| 6               | =====      | 6                 |
| 7               | =====      | 7                 |
| 8               | =====      | 8                 |
| 9               | =====      | 9                 |
| SHELL           | DRAIN WIRE | SHELL             |

|   |              |   |
|---|--------------|---|
| PART NO   CAB-09GW/2-S  | SHEET NO   1 | THIRD ANGLE PROJECTION  |
| TITLE: DB9 PIN MALE TO DB9 PIN FEMALE<br>ASSEMBLY TYPE,BEIGE COLOR,L:2M |              | SCALE   N.T.S   DRAWN BY & DATE   |
|   |              | SIZE   A4   CHECKED BY & DATE   |
| DWN NO   D-CAB-09GW/2-S   |              | UNIT  |
|   |              | <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH   APPROVED BY & DATE |

