

Grease TF

Protects against weathering, preserves surfaces, rubber, plastics, covers a wide range of operating temperatures: from -40°C to 250°C, features a very good chemical resistance to oxidation, water solutions of acids, bases, sulfur dioxide, ammonia.

Physicochemical properties	
Physical state	solid
Colour	white
Density at 20°C	1,0 - 1,1 g/cm ³
Operating temperature range	-40 do 250°C
Flash point	300°C
Water solubility	don't dissolve in water

Application:

- printers, photocopiers, facsimile machines, gearboxes, scanners, audio-video equipment
- sanitary equipment: traditional lever valves; seals, connectors, taps, valves, joints, etc.
- clean lubrication: in the paper, textile and food industry
- automotive industry: for the lubrication of cables in the armour of locks, hinges, bushings, bolts
- the formulation effectively prevents friction and is an ideal protection against corrosion and freezing
- electric devices suspended in air
- maintenance of tourist and sports equipment such as: bicycles and inline skates
- in print shops

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
3,5 g	tube	10/300	ART.AGT-064
20 g	plastic box	8	ART.AGT-065
60 g	plastic box	8	ART.AGT-066
65 ml	squeezer	6	ART.AGT-081
1 kg	plastic box	1	ART.AGT-067

Warehousing:

Store in a well-ventilated, cool and dry place. Protect against sunlight exposure.