



### SPECIFICATIONS

#### Electrical

Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000MΩ/ min.  
 Dielectric Withstanding Voltage: 1500V AC/ min.  
 Contact Resistance: 10mΩ/ max.

#### Material

Material: Nylon66, UL94V-2  
 Terminal Material: Brass/ Tin-plated

Poles	Dimension mm (in.)	
	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.86	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52
13	47.52	51.48
14	51.48	55.44
15	55.44	59.40
16	59.40	63.36
17	63.36	67.32
18	67.32	71.28
20	75.24	79.20

RoHS Compliant		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.5 .00 ± 0.35 ANG. ±	PART NAME 品名 3.96mm WAFER RIGHT ANGLE TYPE 1XXXP WITH LOCKING RIBS TIN PLATED WHITE COLOR ROHS
DWG. 製圖 Betty	SCALE 比例 參考 UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 W2400-XXPRYTWOR
DATE 制表日 2012/04/20	PAGE 張數 1 OF 1	REV. 版次 B	