

Digital Storage Oscilloscopes

UTD2025CL



Features:

- 1、Dual analog channels width range 1mV/div~20V/div;
- 2、7 inches widescreen LCD displays;
- 3、Special Print Scree Feature;
- 4、Supports plug-and-play USB storage device. Communication with and remote control of computer through the USB device;
- 5、USB drive system software upgrade;
- 6、Storage of waveforms setups and interfaces waveforms and setups reproduction;
- 7、Automatic measurement of 28 waveform parameters;
- 8、Unique waveform recording and replay function;
- 9、Multilingual menu displays.

Specification	UTD2025CL
Channels	2
Bandwidth	25MHz
Sample Rate	250Ms/s
Rise Time	≤14ns
Memory Depth	25kpts
Waveform Acquisition Rate	≥2000wfms/s
Vertical Sensitivity	1mV/div~20V/div
Timebase Range	10ns/div~50s/div
Storage	Setup,Wave,Bitmap
Trigger Modes	Edge, Pluse, Video, Alternate
Interface	USB OTG,Pass/Fail
General Characteristic	
Power	100-240VAC, 40-440Hz
Display	7 Inches 64K Color TFT LCD, 400×240
Product Color	White and Gray
Product Net Weight	2.2 Kg
Product Size (W×H×D)	306mm ×147mm × 122mm
Standard Accessories	Probe×2 (1×,10× switchable),Power Cord, USB Cable, PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 PCs
Standard Carton Measurement (L×W×H)	450mm × 420mm × 280mm
Standard Carton Cross Weight	8.5 Kg