


CONDUCTOR: 1/0.57CCA

INSULATION: HDPE



PVC JACKET

CANULAR

PE CROSS

CONSTRUCTION:

[(1/0.57)\*4P]CCA+"+"PE CROSS

CONSTRUCTION DESCRIPTION :

1. CONDUCTOR: 1/0.57 ± 0.005CCA

ID: 0.98 ± 0.02mm

MATERIAL: HDPE (210)

2. CROSS: 4.3 ± 0.1mm MATERIAL: HDPE (210)

3. STANDING PITCH: 100 ± 10mm STANDING DIRECTION: RIGHT

4. FILLER: 500D NYLON PLASTIC

5. OUTER DIAMETER: 6.0 ± 0.2mm

MATERIAL: 45P PVC (520-6919-45)

COLOR: OFFWHITE

6. MAKING:

NETWORK SYSTEMS CABLE UTP ANSI TIA/EIA 568-B.2-1 23AWG (4PR) OR

ISO/IEC11801 VERIFIED CAT 6 1M (2M, ....., 15M, ....., 305M)

7. PACKING: 305M/R

CORE COLOR :

blue/white&blue

brown/white&brown

orang/white&orang

green/white&green

REMAKE:

1. THE ID AND OD OF THE WIRE MUST BE EXACT, CAN NOT REDUCE THE CENTRE.

2. ALL OF THE MATERIAL FOR THE CABLE ARE COMPLIANT WITH RoHS STANDARD.

3. SPARK TEST OF THE CORE'S VOTAGE: AC/2.5KV

4. THICKNESS OF COAT BY EQUALITY: 0.5mm, THE LEAST THICKNESS: 0.45mm

5. THICKNESS OF CORE BY EQUALITY: 0.2mm, THE LEAST THICKNESS: 0.18mm



VCOM International Ltd.

DRING NO.		PRODUCT NO.		TITLE:						
PK-360				CAT6 UTP 0.57CCA						
APPROVED BY	CHECKED BY	DRAWN BY	CUSTOMER	PAGE	UNIT	SCALE		A/0		2013-02-18
		xiang		1 of 1	mm			REV	RESRIPTION	DATE