



UT58B Modern Digital Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm (0.5\%+1)$
AC Voltage	2V/20V/200V/1000V	$\pm (0.8\%+3)$
DC Current	2mA/20mA/200mA/20A	$\pm (0.8\%+1)$
AC Current	2mA/200mA/20A	$\pm (1\%+3)$
Resistance	200 Ω /2k Ω /20k Ω /2M Ω /20M Ω /200 Ω M	$\pm (0.8\%+1)$
Capacitance	2nF/200nF/100 μ F	$\pm (4\%+3)$
Temperature($^{\circ}$ C)	-40 $^{\circ}$ C ~ 1000 $^{\circ}$ C	$\pm (1\%+3)$
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10M Ω	
Max Display	1999	



UL/CUL Pending

Registered Design No.: 0211977.6M001

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54mm
Product Colour	Body- Grey, Holster - Red
Product Net Weight	351g (including holster)
Product Size	179 x 88 x 39mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip, Multi-Purpose Socket, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	508 x 433 x 326mm (0.072CBM Per Standard Carton)
Standard Carton Gross Weight	22kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.